XJ-F211WN





LampFree. MercuryFree. StressFree.

The Advanced Series XJ-F211WN projector provides vibrant colors and high brightness of 3500 lumens in WXGA (1280 x 800) resolution. LampFree® projectors use Casio's Laser & LED light source that eliminates the risk of downtime due to mercury lamp failure. Dust resistant designs with no lamps or filters to replace provide long lasting performance of up to 20,000 hours with minimal maintenance.

Collaboration and Connection is simplified using Casio's Educational Solutions. One Click Connection enables teachers and students to start class quickly. Wireless features such as PC Remote and Moderator Function allow teachers to project their own PC display or select a student's PC display from anywhere in a classroom. Up to 40 PCs can be connected to the projector at one time and up to 4 PCs displayed on-screen simultaneously.

ducational

olutions

Key Features

- 3500 Lumens
- WXGA (1280 x 800)
- 1.5X Zoom Lens
- 16W Speaker
- Dust Resistant Design
- RJ-45 Network Ready model
- · Wireless Capability (optional YW-41 adapter needed)
- Educational Solutions

LampFree Features

- · Laser & LED Light Source
- · Long Life, 20,000 hour estimated operating life
- No Lamp replacement required
- No Filters to replace
- Low Power Consumption
- Mercury Free
- Instant On 5 seconds to full brightness
- Instant Off no cool down required

Terminal Interface



Note:

For more images visit www.CasioLampFree.com Designed and Manufactured by CASIO in Japan TAA Compliant

SPECIFICATIONS	XJ-F211WN
Native Resolution	WXGA (1280 x 800)
Native Aspect Ratio	16:10
Brightness	3500 Lumens
Display Device	0.65-inch DLP® chip
Contrast Ratio	20,000:1
Lens Type	1.5X Manual Zoom & Focus
Lens Offset	33%
Light Source	Laser & LED
Estimated Light Source Life	Up to 20,000 Hours
Screen Size (Min - Max)	30 to 300-inch diagonal
Projection Range	—
60-inch Screen	5.4 ~ 7.9 ft
100-inch Screen	9.2 ~ 13.5 ft
Minimum Throw Distance	3.0 ft
Throw Ratio	1.32 – 1.93:1
Keystone Correction	Vertical +30° (Auto) / Vertical + or - 30° (Manual)
,	
Color Reproduction	Full Color (Up to 1.07 billion colors)
Power Source	AC100~240V, 50/60Hz
Power Consumption	-
Operating	205 W - Light Control "off" and Bright selected 165 W - Light Control "on" and Light Output 7 selected
Standby	0.12 W (Remote On: Disable) / 1.9 W (Remote On: Enable)
TERMINAL CONNECTIVITY	
Video Signal Compatibility	_
Video Systems Video Systems	NTSC / PAL / PAL-N / PAL-M / PAL60 / SECAM
DTV / HDTV	480i / 480p / 576i / 576p / 720p / 1080i / 1080p
Maximum Computer Input	WUXGA (1920 x 1200) *Reduced Blanking Signal
INPUTS	Waxax (1720 x 1200) Reduced Blanking Signal
	mini D-Sub 15 pin x 1
RGB/Component Video Input	Also use as YCbCr/YPbPr input – commercially available adapter required
HDMI	HDMI Type A x 2, HDCP and Audio Support
Composite Video	Composite Video (RCA) x1
Audio	RCA (R/L) x 1, 3.5mm Stereo Mini Jack x 1
USB Power Supply	Yes, DC 5V 2A
USB Input (Host)	USB Type A x 1 shared with DC SV 2A
Logo Transfer	Micro B (USB1.1) x 1
Wireless Capability	Optional Wireless LAN Adapter (YW-41)
OUTPUTS	Optional Wireless EAN Adapter (1 W-41)
Audio	3.5mm Stereo Mini Jack x1 (variable audio)
AUDIO AND CONTROL SYSTEMS	3.311111 Stelled Willi Jack XT (Valiable addio)
	1/1// / C
Audio System	16W Monaural Speaker
RS-232	RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required
LAN	RJ-45 x 1
Control System Compatibility	AMX / Crestron / Extron
OTHER INFORMATION	44 0505 / 00 000 /
Operating Temp / Humidity	41~95°F / 20~80% (non condensation)
High Altitude Mode	Yes, for operation 5,000~10,000 ft.
Extended Operation (24/7)	Yes, Note: Projector must be turned off once every 24 hours
Rotation Projection	Free Orientation
Closed Captioning	Yes
Remote Control Range	16.4 ft Maximum
Security Compatibility	Kensington™ Compatible / Power On Password
Ceiling Mountable	Yes, available and sold separately by 3rd party vendors
Ceiling Mount Screws	M4 x 4 (not included) / Insert Depth 5-8mm
Limited Warranty	3 years Parts and Labor, plus 3 years or 6,000 hours light source
Included Accessories	Wireless Remote Control / Batteries (AAA x 2) / AC Power Cord / RGB Cable Warranty and Safety Precautions
Optional Accessories	Wireless LAN Adapter YW-41 / Soft Carrying Case YB-2
Cabinet Color	White
Unit Dimensions w/ Projections	11.8 x 11.8 x 3.8 inches
Unit Dimensions w/o Projections	N/A
Weight	8.4 lbs
Carton Dimensions	15.5 x 13.7 x 6.9 inches
Carton Weight	11.7 lbs
UPC Code	8-89232-80096-7
Manufactured In	Japan TAA Compliant
· ·	

©2019 Casio America, Inc. All rights reserved. Casio is a registered trademark of Casio Computer Co., Ltd. In the United States and/or other countries. Specifications were thought to be correct at the time of publication. All specifications and features subject to change without notice. DLP is a trademark of Texas Instruments, XGA is a registered trademark of IBM Corp. in the US. HDMI is a trademark of HDMI Licensing, Ltc. Other product names or company names on this specification brochure are either trademarks or registered trademarks of their respective owners.* Educational Solutions available only with Network models. Optional YW-41 required. C-Connection Software or App required.

