



XJ-A247

SLIM SERIES

LampFree. MercuryFree. StressFree.

The cool-running XJ-A247 Slim Line projector has the ability to run all day, every day in extended-use applications* including digital signage, museum displays and other challenging environments. Run the XJ-A247 worry-free, knowing you will not shorten its expected life or damage the projector's bright, high-impact images. (Projectors must be reset once a day when operated in continuous operation applications).

Super Slim Portable Design

The thinnest, high brightness projector - 1.7 inches thin - the length and width of a sheet of paper and weighs only 5 lbs. Lightweight and easy to carry, take the XJ-A247 projector with you wherever you need it.

Key Features

- 2500 Lumens
- Closed Captioning
- Input/Output Connectivity
- · Built-in 1W speaker
- WXGA (1280 x 800) resolution
- 2 X Power Zoom/Focus Lens
- DLP® Technology

LampFree Features

- · Laser & LED Hybrid Light Source
- Long Life, 20,000 hour estimated operating life
- No Lamp replacement required
- No Down Time
- Low Power Consumption
- Mercury Free
- Quick On (8 seconds to full brightness)
- Instant Off no cool down required

Terminal Interface



WXGA Native Resolution 1280 x 800 Native Aspect Ratio 16:10 2500 lumen Brightness 0.65 -inch DLP® chip Display Device Lens Type 2X Power Zoom & Focus Lens Offset 33% Liaht Source Casio Laser & LED (up to 20,000 hours) Lens Spec F/f F2.29-3.09/f15.9-30.8mm Screen Size (Min-Max) 18 to 300-inch diagonal Projection Range 4.6-9.3ft 60-inch screen 100-inch screen 7.9-15.8ft 2.8ft Minimum Throw Distance 1.15-2.30:1 Throw Ratio Keystone Correction Vertical +30° (Auto) Vertical + or - 30° (Manual) Full color (up to 16.77 million colors) Color Reproduction AC100~240V, 50/60Hz Power Source Power Consumption Bright mode: 155w Operating Eco1 mode: 115W 0.14 W Standby Video Signal Compatibility NTSC/ PAL/ PAL-N/ PAL-M/ PAL60/ SECAM 480i/480p/576i/576p/720p/1080i/1080p UXGA (1600 X 1200) Maximum Computer Input mini D-Sub 15 pin x 1 (Also use as YCbCr/YPbPr input— commercially available adapter required) RGB/Component Video Input HDMI HDMI Type A x 1 (480p~1080p) Yes USB Display Composite Video Stereo Mini x 1 (shared with Stereo Audio) Built-in Memory Yes, 2GB (PDF, JPEG, BMP, PNG, GIF, AVI, MOV, MP4) Type A (USB 2.0) x 1 USB Logo Transfer Micro B(USB1.1) x1 Wireless Capability Wirelesss LAN Adapter (YW-40) is included with USB Models Stereo Mini x 1, Variable Audio Audio Audio system 1W x 1 Monaural Speaker Control Terminal RS-232C (Mini Din) x 1 Optional YK-60 cable required and sold separately Control System Compatibility AMX, Crestron, Extron, SP Controls, PJLink OTHER INFORMATION Usage Environment 41~95°F / 20~80% (non condensation) Operating Temp/Humidity High Altitude Mode Yes (for operation 5,000~10,000 ft) Closed captioning Yes Extended operation (24 x 7) Yes – Note: Projector must be turned off once every 24 hours Rotation Projection 90 degrees Left/Right (Portrait) Only Remote Control Range 16.4 ft Maximum Security Compatibility Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M3 x 3(not included) Insert Depth4-6mm Ceiling Mountable Ceiling Mount Screws 3 years Parts and Labor plus 3 years or 6,000 hours light source, see Warranty Statement included with product for complete details.

Wireless remote control, YW-40 adapter, 6" RGB cable, AV cable, 6" AC Power Cord, Carry Limited Warranty Included Accessories Bag, Setup Manual (Printed) Included Software Network Connection (Windows and Mac) EZ-Converter FA (Windows) Ontional Accessories YK-60 (RS-232C adapter) Cabinet Color White/Light Grey Trim Dimension (W x D x H) 11.7 x 8.3 x 1.7 inches Including Projections 11.7 x 8.3 x 1.6 inches **Excluding Projections** 5.1lbs Weight Packing Information 15.0 x 6.2 x 10.4 inches Carton Dimensions 10.1 lbs 0-79767-46682-4

© 2016 Casio America, Inc. All rights reserved. Casio is a registered trademark of Casio Computer Co., Ltd. In the United States and/or other countries. Specifications were thought to be correct at time of publication. All specifications and features are subject to change without notice. DLP, the DLP logo and the DLP medallion are trademarks of Texas Instruments. XGA is a registered trademark of International Business Machines Corporation in the United States. HDMI is a trademark or registered trademark of HDMI Licensing, LLC. Other product names or company names on this specification brochure are either trademarks or registered trademarks of their respective owner

Japan TAA Compliant

* Extended Use Applications are defined as operation of 10 hours per day for 5 or more days per week. Under these conditions the light source warranty is one (1) year or 6000 hours

Designed and Manufactured by Casio in Japan TAA Compliant

LIPC Code

Manufactured in