



XJ-UT351W / WN

ULTRA SHORT THROW SERIES

LampFree. MercuryFree. StressFree.

Casio's Ultra Short Throw LampFree® projectors incorporate Laser & LED Technology to produce images of impressive brightness. They have a long lasting lifespan of up to 20,000 hours with reduced electricity consumption and no lamps or filters to replace.

With their Ultra-Short Throw lens, the XJUT351W and XJ-UT351WN can project brilliant, crisp, shadow-free images of up to 110" diagonal with a full assortment of connectivity and features. The built-in short throw lens and advanced mirror system provides an extremely close throw ratio (0.28:1) and projects an 80" image from just 1.5 feet away.

Key Features

- 3500 Lumens
- Ultra Short Throw Ratio (.28:1)
- Dust Resistant Design
- Built-in 16W speaker
- Expanded input/output connectivity
- High Contrast Ratio of 20,000:1
- DLP® Technology

LampFree Features

- Laser & LED Hybrid Light Source
- · Long Life, 20,000 hour estimated operating life
- No Lamp replacement required
- No Filters
- Less Down Time
- Low Power Consumption
- · Mercury Free
- Quick On (5 seconds to full brightness)
- · Instant Off no cool down required

XJ-UT351WN Only

- RJ-45 Wired LAN
- Wireless Capability
- · Optional Wireless Adaptor (YW-40) Available

CASIO Projector Specifications	XJ-UT351W XJ-U	T351WN
	WXGA	
Native Resolution	1280 x800	
Native Aspect Ratio	16:10	
Brightness	3500 lumens	
Display Device	0.65" DLP® chip	
Contrast Ratio	20.000:1	
	Fixed Zoom/Manual Focus	
Lens Type	Fixed lens F2.3/f4.2	
Lens Spec F/f		
Lens Offset	70%	
Light Source	Laser & LED (Up to 20,000 Hours)	
Projection Screen Size (Min-Max)	50 to 110-inch diagonal	
Projection Range		
60-inch screen	0.4 ft	
100-inch screen	1.3 ft	
Minimum	0.2 ft	
Throw Ratio (60 inches)	0.28:1	
Keystone Correction	Vertical and Horizontal + or - 5° (Manual)	
Color Reproduction	Full color (1.07 billion colors)	
Power Consumption		
Operating (Default) Light Output 7	185W	
Operating (Minimum) Light Output 1	125W	
Operating (Bright)	225W	
Standby (Remote Off/On)	0.23 W/2.6 W	
TERMINAL CONNECTIVITY	0.23 W/2.0 W	
	WIII/CA (1000 1000)	
Maximum Signal Input	WUXGA (1920 x 1200)	
Analog input terminal	mini D-Sub 15 pin x 2	
RGB/Component Video Input	mini D-Sub 15 pin x 1 Also use as YCbCr/YPbPr input— co available adapter required	ommercially
HDMI Input	HDMI Type A x 2 (480p-1080p)	
USB Input		Type A x 1
Composite Video Input	Video (RCA) x1, S Video x 1	
Audio Input	RCA (R/L) x1, Stereo Mini x 2	
USB Power Supply	DC 5V / 2A	
Microphone Input	3.5 mm Mini	
Built-in Memory	_	
Logo Transfer	USB 1.1 Micro-B x 1	
Audio Output	Stereo Mini x 1, Mini D-sub 15 pin x 1	
Monitor Output	mini D-Sub 15 pin x 1	
Control (Serial) Terminal	RS-232C (D sub 9 pin) x 1 Cross Cable (Null Modem) i	reauired
Built in Speaker	16W Monaural Speaker	
LAN		-45 x 1
Wireless Capability		AN Adapter (YW-4
OTHER INFORMATION	Ave	
Operating Temperature	41º - 95º F	
Operating Humidity	20% - 80% (non-condensation)	
Remote Control Operating Range	16.4 ft Max.	
Kensington / Power On Password	Yes	
	ies	
Product Dimension (W x D x H)	1/ 5 - 121 - / 0	
Excluding Projections	16.5 x 13.1 x 6.0 inches	
Weight	13.23lbs	
Packing Information		
Carton Dimensions	20.9 x 16.2 x 10.2 inches	
Carton Weight	19.4 lbs	
	Remote control, 6' RGB cable, 6' AC Power Cor	-d
Included Accessories		
Included Accessories Mounting Screws	M4 x 4 (not included) Insert depth (5-8 mm))
	M4 x 4 (not included) Insert depth (5-8 mm)	

Terminal Interface





XJ-UT351W

XJ-UT351WN

© 2017 Casio America, Inc. All rights reserved. Casio is a registered trademark of Casio Computer Co., Ltd. In the United States and/or other countries. Specifications were thought to be correct at time of publication. All specifications and features are subject to change without notice. DLP, the DLP logo and the DLP medallion are trademarks of Texas Instruments. XGA is registered trademark of International Business Machines Corporation in the United States. HDMI is a trademark or registered trademark of HDMI Licensing, LLC. Other product names or company names on this specification brochure are either trademarks or registered trademarks of their respective owners.

Designed and Manufactured by Casio in Japan TAA Compliant